


JUNCTIONS SKYLIGHT



(minimum slope 14°(25%))

R=overlap, see installation guide of VMZ Standing Seam



overview

For the expansion of the VMZINC®, we cover the skylight with a independent flashing. The above standing seam sheets are welted to this flashing. This flashing is laterally locked in the VMZ Standing Seam.



1. VMZ Standing Seam in VMZINC® PLUS
2. VMZ Saddle piece
3. insulated metal panel, in accordance with specifications.
4. skylight flashing
5. roof boarding
6. VMZINC Membrane
7. sheet clip in VMZINC® PLUS, th=0.7 mm, w=80 mm, 2 per m
8. dubble welt in VMZINC® PLUS, continuously soldered
9. flashing to witch the VMZ Standing Seam is fixed
10. water conductor piece, slope min 0.5°

VMZINC

STANDARD DETAIL

Ref : VMZ-SN-CP-RAA-b1

Date : 2022

VM Building Solutions UK Collier House, Mead Lane, Hertford, SG13 7AX Tel: 0203.445.5640

VM BUILDINGSOLUTIONS

The confidential information in this design document is protected by intellectual property rights and is the sole property of VM Building Solutions. Any use/ distribution of the design, in whole or in part, not related to the installation of VM Building Solutions products, is unauthorized and strictly prohibited. This study is carried out free of charge, based on the elements in possession of the Project Support Bureau of VM Building Solutions. The author is responsible for adaptation to the definitive characteristics of the project. Work must be carried out in accordance with the 'Design and specification requirements' from the last edition of VMZINC®, produced by VM Building Solutions.