



RIDGE / HIP G3

Attention : for hip, distance between 2 standing seam maximum 940 mm !



1. VMZINC Membrane
2. Metdeck composite panel, incorporating an WBP plywood factory bonded to the Resol foam
3. decompression strip G3, to order with G3 ridge
4. vapour barrier - type Aluminium foil with bitumen
5. VMZ standing seam in VMZINC® PLUS
6. VMZ Ridge clip G3, fixed part
7. VMZ Ridge clip G3, moving part
8. VMZ Ridge G3
9. fixing, in accordance with specifications
10. vapour barrier support (plywood or structural metal deck)



All VMZ Standard elements are tested and validated by Umicore, to be exclusively used with VMZINC® Products. their usage with other products is granted by the roofer.

VMZINC

STANDARD DETAIL

Ref : VMZ-SN-MD-NO-G3-01 Date : 2022

VM Building Solutions UK Collier House, Mead Lane, Hertford, SG13 7AX Tel: 0203.445.5640

VM BUILDING SOLUTIONS

The confidential information in this design document is protected by intellectual property rights and is the sole property of VM Building Solutions. Any use/distribution of the design, in whole or in part, not related to the installation of VM Building Solutions products, is unauthorized and strictly prohibited. This study is carried out free of charge, based on the elements in possession of the Project Support Bureau of VM Building Solutions. The author is responsible for adaptation to the definitive characteristics of the project. Work must be carried out in accordance with the 'Design and specification requirements' from the last edition of VMZINC®, produced by VM Building Solutions.